



minipack® - torre
Packaging machines and systems

ECOMODULAR

**MANUAL PACKAGING MACHINE - L-SEALING - ENTRY LEVEL - SEALING BAR
540X390 MM**



DESCRIPTION

A wide sealing surface, as much as 570x420 mm, is the distinctive feature of **ECOMODULAR**, the easy and user-friendly manual angular packaging machine. The sealing blade at the bottom has a simple and effective temperature control system and allows for optimal sealing with any kind of film. Available in the

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



standard (with a fixed plate) and automatic version (with a product evacuation belt), this machine by **minipack®-torre** is completed by **TUNNEL 50**. This solution creates perfectly heat-shrunk packaging and meets any need in terms of packaging.

TECHNICAL FEATURES

Electrical power supply	V	230
MAX power installed	kW	2.2
Hourly output	p/h (pph)	0-550
Available dimensions of the sealing bars	mm	540x390
MAX Reel Dimensions (diameter)	mm	250
MAX Reel Strip Dimensions (width)	mm	600
Work surface height	mm	930
Machine weight (Net/Gross)	kg	101/130
Machine dimensions with the sealing fr. open	mm	1570x730x h.1400
Machine dimensions with the sealing fr. closed	mm	1570x730x h.1100

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.